

PDFlib Migration Guide

Latest PDFlib version covered in this document: PDFlib 10.0 Beta 1

The PDFlib API generally remains compatible among major releases. Sometimes API methods are phased out and replaced with an improved successor which is more general or more powerful than the old method. In these situations the new PDFlib version declares the old method as deprecated without changing the functionality in any way. The new method is always preferable. New code should not use deprecated API methods; existing code should switch to the replacement method as soon as possible. Deprecated methods may be removed in a future release.

PDFlib 10 removes several old features which have been deprecated in earlier versions. Legacy applications which still use these features must apply the replacements detailed in this document before they can switch to PDFlib 10. In most cases one-to-one replacement methods or options are available.

1 Check for deprecated PDFlib API Features

Note PDFlib 10 contains almost no deprecated features. You can use PDFlib 9.3 to check whether your application uses legacy features from earlier PDFlib versions.

1.1 Identify deprecated API Method Calls at Compile Time

Deprecated API calls can be identified at compile time for some language bindings. Note that only warnings are emitted; the code can still be compiled successfully. Nevertheless it is strongly recommended to replace deprecated API methods with the recommended replacement method.

Java binding. The *pdflib.jar* module is created from source code which contains *@Deprecated* annotations and *@deprecated* Javadoc comments for all deprecated API methods so that the compiler can warn about the use of deprecated methods. The Java compiler emits a warning similar to the following:

```
javac -classpath pdflib.jar:. image.java
Note: image.java uses or overrides a deprecated API.
Note: Recompile with -Xlint:deprecation for details.
```

If you supply the compiler option *-Xlint:deprecation* the name and location of the deprecated API methods are shown:

```
javac -classpath pdflib.jar:. -Xlint:deprecation image.java
image.java:37: warning: [deprecation]
    get_value(String,double) in pdflib has been deprecated
    p.get_value( "major", 0.000000);
      ^
```

The Javadoc documentation for PDFlib lists all deprecated methods along with the recommended replacement method, e.g.




Fig. 1.1
Presentation of deprecated Java
API methods in Eclipse

```
double get_value(java.lang.String key, double modifier) Deprecated.
Use PDF_get_option().
```

In Eclipse you must attach *pdflib.jar* as library to make information about deprecated API methods available to the integrated Java compiler. If deprecated API methods are found in your code, the name of the deprecated method is displayed with a strike-out, and a pop-up box informs about the method's status (see Figure 1.1). These messages are also listed in the *Problems* view.

.NET and .NET Core bindings with Visual Studio. The PDFlib package is created from source code which contains »Deprecated« comments for all deprecated API methods so that calls to deprecated methods are marked with an underline, and IntelliSense pop-ups are shown with a warning for calls to deprecated API methods when editing the code.

The PDFlib assembly also contains »Obsolete« attributes for all deprecated API methods so that the compiler can warn about the use of deprecated API methods.

Visual Studio emits warnings for calls to deprecated API methods if warning level 2 is enabled in *Project, Properties, Build, Errors and warnings*. The warning includes the recommended replacement method:

```
image.cs(37,13): warning CS0618: 'PDFlib_dotnet.PDFlib.get_value(string, double)' is
obsolete: 'Deprecated, use PDF_get_option().'
```

.NET Core binding with command-line compiler. The *dotnet run* command also emits warnings for deprecated API methods in the compilation phase, provided the *<WarningLevel>* element in the project file is set to 2 or higher:

```
image.cs(37,13): warning CS0618: 'PDFlib.get_value(string, double)' is obsolete:
'Deprecated, use PDF_get_option().'
```

C++ binding with Visual Studio, GCC or Clang. The header file *pdflib.hpp* contains suitable attributes for all deprecated API methods so that the compiler can warn about the use of deprecated methods.

Visual Studio emits warnings for deprecated API calls if warning level 3 is enabled in *Project, Properties, Configuration Properties, C/C++, General/Warning Level: Level 3 (/W3)*:

```
image.cpp(33) : warning C4996: 'pdflib::basic_PDFlib<pstring,conv>::get_value':
was declared deprecated
           with
           [
               pstring=std::wstring,
               conv=pdflib::NoOpConverter<std::wstring>
           ]
```

With GCC and Clang the option `-Wdeprecated-declarations` must be supplied:

```
image.cpp:33:25: warning: 'double pdflib::basic_PDFlib<pstring, conv>::get_value(const
pstring&, double) [with pstring = std::__cxx11::basic_string<wchar_t>; conv =
pdflib::NoOpConverter<std::__cxx11::basic_string<wchar_t> >]' is deprecated
[-Wdeprecated-declarations]
    p.get_value(L"major", 0);
```

C binding with Visual Studio, GCC or Clang. The `pdflib.h` header file contains suitable attributes for all deprecated API methods so that the compiler can warn about the use of deprecated methods.

Visual Studio emits warnings for deprecated API calls if warning level 3 is enabled in *Project, Properties, Configuration Properties, C/C++, General/Warning Level: Level 3 (/W3)*:

```
image.c(44): warning C4996: 'PDF_get_value': was declared deprecated
```

With GCC and Clang the option `-Wdeprecated-declarations` must be supplied:

```
image.c:44:2: warning: 'PDF_get_value' is deprecated [-Wdeprecated-declarations]
    PDF_get_value(p, "major", 0);
```

1.2 Identify deprecated API Method Calls at Runtime

Using the methods below you can create a list of deprecated API method calls at run-time. These API methods must be replaced in the application; see Section 2.1, »Deprecated PDFlib API Methods«, for details.

Logging for all language bindings. Calls to deprecated API methods are identified in the log file for all language bindings with logging class `api=1`. It can be set as follows (see PDFlib API Reference for more details on logging):

```
p.set_option("logging={filename=deprecated.log classes={api=1}}");
```

With this setting the log file contains an entry for all calls to deprecated API methods, e.g.

```
PDF_get_value(p_0x2599c20, "major", 0.000000)
[PDF_get_value() is deprecated since PDFlib 9]
```

PHP language binding. The PDFlib extension module for PHP contains information about deprecated API methods so that the PHP interpreter can warn about deprecated methods. Depending on the PHP configuration warnings about deprecated method calls are written to the configured PHP error log file, the Web server log file, the Windows event log/system log, or `stderr/stdout`. The following directive in `php.ini` configures the log file:

```
error_log = /var/log/php.errors
```

The default is empty; see www.php.net/manual/en/errorfunc.configuration.php for details.

Whether or not warnings about deprecated calls are written to the log file depends on the `error_reporting` directive which must include `E_DEPRECATED`, e.g.

```
error_reporting = E_ALL
```

See www.php.net/manual/en/function.error-reporting.php for details. Once logging for deprecated calls is configured, PHP reports all deprecated calls as follows in the PHP error log file (not the PDFlib log file):

```
PHP Deprecated:  PDFlib::get_value(): Deprecated, use PDF_get_option(). in /home/bind/php/image.php on line 37
```

Perl language binding. The PDFlib module for Perl emits warnings about deprecated API methods at runtime if the predefined warning category *deprecated* is enabled, which is true by default. Perl emits a warning similar to the following:

```
PDF_get_value(): Deprecated, use PDF_get_option(). at image.pl line 31.
```

Use the following instruction or the `-X` command-line option of the Perl interpreter to disable warnings about deprecated API methods on a module basis:

```
no warnings 'deprecated';
```

Warnings for deprecated API methods can be enabled on a module basis with the following instruction in the application code:

```
use warnings 'deprecated';
```

or by calling the Perl interpreter with the `-W` command-line option.

1.3 Identify deprecated Options

All language bindings. Deprecated options cannot be detected at compile time, but only at runtime. They can be identified in the logging output with the logging class *api=1* which can be set as follows:

```
p.set_option("logging={filename=deprecated.log classes={api=1}}");
```

With this setting the log file contains a message for all API calls with deprecated options, e.g.

```
PDF_create_annotation(p_0x1529c20, 100.000000, 400.000000, 400.000000, 500.000000,
"FileAttachment", "filename=foo.jpg mimetype=image/jpeg")
[Option "filename" is deprecated since PDFlib 9]
[Option "mimetype" is deprecated since PDFlib 9]
```

These options must be replaced in the application; see Section 2.2, »Deprecated Options and Keywords which are no longer available in PDFlib 10«, for details.

2 Deprecated PDFlib API Features

2.1 Deprecated PDFlib API Methods

Table 2.1 lists deprecated API methods which are no longer available in PDFlib 10. Applications must use the replacement methods shown in the table.

Table 2.1 *Deprecated PDFlib API methods and their replacements*

deprecated API method	deprecated since	replacement method
PDF_add_bookmark() PDF_add_bookmark2()	PDFlib 6	PDF_create_bookmark(); the parent and open parameters correspond to the same-named options
PDF_add_launchlink()	PDFlib 6	PDF_create_action() with type=Launch and PDF_create_annotation() with type=Launch
PDF_add_locallink()	PDFlib 6	PDF_create_action() with type=GoTo and PDF_create_annotation() with type=Link
PDF_add_note() PDF_add_note2()	PDFlib 6	PDF_create_annotation() with type=Text
PDF_add_pdflink()	PDFlib 6	PDF_create_action() with type=GoToR and PDF_create_annotation() with type=Link
PDF_add_thumbnail()	PDFlib 9	none; not functional since PDFlib 9
PDF_add_weblink()	PDFlib 6	PDF_create_action() with type=URI and PDF_create_annotation() with type=Link
PDF_attach_file() PDF_attach_file2()	PDFlib 6	PDF_create_annotation() with type=FileAttachment; the description parameter corresponds to the contents option, the author parameter to the title option and the icon parameter to the iconname option.
PDF_begin_glyph()	PDFlib 9	PDF_begin_glyph_ext()
PDF_begin_page()	PDFlib 6	PDF_begin_page_ext()
PDF_begin_pattern()	PDFlib 9	PDF_begin_pattern_ext()
PDF_begin_template()	PDFlib 7	PDF_begin_template_ext()
PDF_boot() (only C/C++)	PDFlib 7	none; was never functional
PDF_close()	PDFlib 6	PDF_end_document()
PDF_close_pdi()	PDFlib 7	PDF_close_pdi_document()
PDF_end_page()	PDFlib 6	PDF_end_page_ext()
PDF_end_template()	PDFlib 8	PDF_end_template_ext()
PDF_findfont()	PDFlib 5	PDF_load_font()
PDF_get_majorversion() PDF_get_minorversion()	PDFlib 4	PDF_get_option() with keys major/minor
PDF_get_parameter() PDF_get_value()	PDFlib 9	For many keys the same-named option of PDF_get_option() can be used; see Table 2.3 for keys which require other replacement methods.
PDF_get_pdi_parameter() PDF_get_pdi_value()	PDFlib 7	PDF_pcos_get_string() and PDF_pcos_get_number() with pCOS paths according to Table 2.2
PDF_initgraphics()	PDFlib 9	PDF_set_graphics_option() with option initgraphicsstate
PDF_open_CCITT()	PDFlib 5	PDF_load_image() with type=ccitt
PDF_open_file()	PDFlib 6	PDF_begin_document() and PDF_end_document()
PDF_open_image() PDF_open_image_file()	PDFlib 5	PDF_load_image()
PDF_open_mem()	PDFlib 6	PDF_begin_document() with empty filename and PDF_get_buffer()

Table 2.1 *Deprecated PDFlib API methods and their replacements*

deprecated API method	deprecated since	replacement method
<code>PDF_open_pdi()</code>	PDFlib 7	<code>PDF_open_pdi_document()</code>
<code>PDF_place_image()</code>	PDFlib 5	<code>PDF_fit_image()</code> with <code>dpi=none</code>
<code>PDF_place_pdi_page()</code>	PDFlib 5	<code>PDF_fit_pdi_page()</code>
<code>PDF_set_border_color()</code>	PDFlib 6	<code>PDF_create_annotation()</code> with option <code>annotcolor</code>
<code>PDF_set_border_dash()</code>	PDFlib 6	<code>PDF_create_annotation()</code> with option <code>dasharray</code>
<code>PDF_set_border_style()</code>	PDFlib 6	<code>PDF_create_annotation()</code> with options <code>borderstyle</code> and <code>linewidth</code>
<code>PDF_set_parameter()</code> <code>PDF_set_value()</code>	PDFlib 9	For many keys the same-named option of <code>PDF_set_option()</code> can be used; see Table 2.3 for keys which require other replacement methods.
<code>PDF_setdash()</code> <code>PDF_setdashpattern</code>	PDFlib 9	<code>PDF_set_graphics_option()</code> and other methods with graphics appearance options with option <code>dasharray</code> and <code>dashphase</code>
<code>PDF_setflat()</code>	PDFlib 9	<code>PDF_set_graphics_option()</code> or <code>PDF_create_gstate()</code> with option <code>flatness</code>
<code>PDF_setgray()</code> <code>PDF_setgray_fill()</code> <code>PDF_setgray_stroke()</code>	PDFlib 4	<code>PDF_set_graphics_option()</code> and other methods with color options
<code>PDF_setlinejoin()</code>	PDFlib 9	<code>PDF_set_graphics_option()</code> or <code>PDF_create_gstate()</code> with option <code>linejoin</code>
<code>PDF_setlinecap()</code>	PDFlib 9	<code>PDF_set_graphics_option()</code> or <code>PDF_create_gstate()</code> with option <code>linecap</code>
<code>PDF_setmiterlimit()</code>	PDFlib 9	<code>PDF_set_graphics_option()</code> or <code>PDF_create_gstate()</code> with option <code>miterlimit</code>
<code>PDF_setpolydash()</code>	PDFlib 5	<code>PDF_set_graphics_option()</code> and other methods with graphics appearance options with option <code>dasharray</code>
<code>PDF_setrgbcolor()</code> <code>PDF_setrgbcolor_fill()</code> <code>PDF_setrgbcolor_stroke()</code>	PDFlib 4	<code>PDF_set_graphics_option()</code> and other methods with color options
<code>PDF_show_boxed()</code> <code>PDF_show_boxed2()</code>	PDFlib 6	single lines: <code>PDF_fit_textline()</code> multi-line formatting: <code>PDF_add/create_textflow()</code> and <code>PDF_fit_textflow()</code> with options <code>minspacing=100%</code> <code>maxspacing=10000%</code> <code>nofitlimit=100%</code> <code>shrinklimit=100%</code> to achieve similar formatting If <code>PDF_show_boxed()</code> has been called with <code>mode=fulljustify</code> use the following <code>Textflow</code> options: <code>lastalignment=justify</code> <code>alignment=justify</code>
<code>PDF_shutdown()</code> (only C/C++)	PDFlib 7	none; was never functional
<code>PDF_utf16_to_utf8()</code> <code>PDF_utf8_to_utf16()</code> <code>PDF_utf32_to_utf8()</code> <code>PDF_utf8_to_utf32()</code> <code>PDF_utf16_to_utf32()</code> <code>PDF_utf32_to_utf16()</code>	PDFlib 8.1	<code>PDF_convert_to_unicode()</code> with appropriate parameter <code>inputformat</code> and option <code>outputformat</code>
<code>PDF_xshow()</code> (only C/C++)	PDFlib 9	<code>PDF_fit_textline()</code> with option <code>xadvancelist</code>

pCOS paths for deprecated PDF_get_pdi_value/parameter() methods. The deprecated (as of PDFlib 7) methods *PDF_get_pdi_value()* and *PDF_get_pdi_parameter()* use custom keys for addressing objects in a PDF documents. When switching to *PDF_pcos_get_number()* and *PDF_pcos_get_string()* these keys must be replaced with the corresponding pCOS paths according to Table 2.2 (see pCOS Path Reference for details).

Table 2.2 pCOS paths as replacements for deprecated keys of PDF_get_pdi_value() and PDF_get_pdi_parameter()

key for PDF_get_pdi_value() and PDF_get_pdi_parameter()	pCOS path for PDF_pcos_get_number() and PDF_pcos_get_string()
vdp/blockcount	length:pages[...]/blocks
/Root/Pages/Count	length:pages
width, height	pages[...]/width, pages[...]/height
/Rotate	pages[...]/Rotate
version	pdfversion
/CropBox, /BleedBox, /ArtBox, /TrimBox, /MediaBox	pages[...]/CropBox[0] for llx, pages[...]/CropBox[1] for lly, pages[...]/CropBox[2] for urx, pages[...]/CropBox[3] for ury etc.
vdp/Blocks/<name>/<property>	pages[...]/blocks/<name>/<property>
vdp/Blocks[...]/<property>	pages[...]/blocks[...]/<property>
vdp/Blocks/<name>/Custom/<property>	pages[...]/blocks/<name>/Custom/<property> or pages[...]/blocks[...]/Custom/<property>
isempty	pages[...]/isempty
filename	filename
/Info/<key>	/Info/<key>
tagged	tagged
pdfx	pdfx

Replacements for deprecated global values and parameters. In most cases the deprecated methods *PDF_set/get_value()* and *PDF_set/get_parameter()* can be replaced with *PDF_set/get_option()* and the previous parameter *key* as option name. Table 2.3 lists parameters which must be replaced with other methods and options.

Table 2.3 *Deprecated global parameters for PDF_set/get_value() and PDF_set/get_parameter() and their replacements*

<i>deprecated parameter</i>	<i>deprecated since</i>	<i>replacement method and option</i>
resource categories		
Encoding, FontAFM, FontOutline, FontPFM, HostFont, ICCProfile, resourcefile, searchpath	PDFlib 9	same-named options of <i>PDF_set_option()</i> ; multiple entries can be set with a single call; <i>PDF_get_option()</i> : use option resourcenum to iterate over all values
StandardOutputIntent	PDFlib 9	none; use embedded or referenced ICC profile as output intent
document properties		
compatibility	PDFlib 6	<i>PDF_begin_document()</i> with option compatibility
userpassword, masterpassword, permissions	PDFlib 6	<i>PDF_begin_document()</i> with options userpassword, masterpassword, permissions
pdfx	PDFlib 6	<i>PDF_begin_document()</i> with option pdfx
base	PDFlib 6	<i>PDF_begin_document()</i> with option uri
openmode	PDFlib 6	<i>PDF_begin_document()</i> with option openmode
openaction	PDFlib 6	<i>PDF_begin/end_document()</i> with option destination; the following deprecated option keywords must be replaced: fitbbox: use type=fitvisible fitheight: use type=fitheight left=0 fitpage: use type=fitwindow fitwidth: use type=fitwidth top=10000 retain: use type=fixed
hidetoolbar, hidemenubar, hidewindowui, fitwindow, centerwindow, displaydoctitle, nonfullscreenpagemode, direction, viewarea, viewclip, printarea, printclip	PDFlib 6	<i>PDF_begin/end_document()</i> with option viewer-preferences and respective suboptions; the suboptions viewarea, viewclip, printarea, printclip are deprecated in PDF 2.0 (see Table 2.5)
page properties		
pageheight, pagewidth in <i>PDF_set_parameter()</i>	PDFlib 6	<i>PDF_begin/end_page_ext()</i> with options pagewidth and pageheight
ArtBox, BleedBox, CropBox, TrimBox	PDFlib 6	<i>PDF_begin/end_page_ext()</i> with options artbox, bleedbox, cropbox, trimbox
duration, transition	PDFlib 6	<i>PDF_begin/end_page_ext()</i> with same-named options
color		
defaultgray, defaultrgb, defaultcmyk	PDFlib 6	<i>PDF_begin/end_page_ext()</i> with options defaultgray, defaultrgb, defaultcmyk
setcolor:iccprofilegray/rgb/cmyk	PDFlib 9	graphics appearance options iccprofilegray/rgb/cmyk
preserveoldpantonenames	PDFlib 9.3	none; old-style PANTONE color names are no longer in use

Table 2.3 *Deprecated global parameters for PDF_set/get_value() and PDF_set/get_parameter() and their replacements*

<i>deprecated parameter</i>	<i>deprecated since</i>	<i>replacement method and option</i>
font handling		
autosubsetting, subsetlimit, subsetminsize, fontstyle, unicodemap	PDFlib 7	PDF_load_font() with same-named options
ascender, ascenderfaked, capheight, capheightfaked, descender, descenderfaked, fontencoding, fontname, fontmaxcode, xheight, xheightfaked	PDFlib 7	PDF_info_font() with same-named keywords; for the numerical values fontsize=1 must be supplied; parameter fontencoding: use keyword encoding
autocidfont	PDFlib 8	none; not functional since PDFlib 9
monospace	PDFlib 7	none; only for the obsolete concept of standard CJK fonts
text output		
charref, charspacing, decoration-above, escapesequene, fakebold, font, fontsize, glyphcheck, horiz-scaling, italicangle, kerning, leading, overline, strikeout, strokewidth, textformat, text-rendering, textrise, underline, underlineposition, underlinewidth, wordspacing	PDFlib 9	PDF_set_text_option(), PDF_fit/info_textline(), PDF_fill_textblock() and PDF_add/create_textflow() with same-named options
images		
honoriccprofile	PDFlib 8.2	PDF_load_image() with option honoriccprofile
renderingintent	PDFlib 8.2	PDF_load_image() with option renderingintent
imagewidth, imageheight, image:iccprofile, orientation, resx, resy	PDFlib 8	PDF_info_image() with same-named options
graphics state		
fillrule in PDF_set_parameter()	PDFlib 9.3	PDF_set_graphics_option() with option fillrule
inheritgstate	PDFlib 6	none; not functional
interactive elements		
bookmarkdest	PDFlib 6	PDF_create_bookmark() with options action, destination, fontstyle and textcolor
launchlink:parameters launchlink:operation launchlink:defaultdir	PDFlib 6	PDF_create_action() with options parameters, operation, and defaultdir; however, these are deprecated in PDF 2.0 (see Table 2.5)
miscellaneous		
flush	PDFlib 6	PDF_begin_document_callback() with option flush
pdiusebox	PDFlib 6	PDF_open_pdi_page() with option pdiusebox
iccwarning, fontwarning, glyphwarning, imagewarning, pdiwarning, warning	PDFlib 7	corresponding API method with option errorpolicy
openwarning	PDFlib 6	PDF_begin_document() with option errorpolicy

Table 2.3 *Deprecated global parameters for PDF_set/get_value() and PDF_set/get_parameter() and their replacements*

<i>deprecated parameter</i>	<i>deprecated since</i>	<i>replacement method and option</i>
honorlang	PDFlib 8	PDF_set_option() with option filenamehandling=honorlang
trace, tracefile, tracemsg	PDFlib 7	PDF_set_option() with option logging
logmsg	PDFlib 9	PDF_set_option() with option userlog
nodemostamp	PDFlib 9	PDF_set_option() with option avoiddemostamp
string	PDFlib 9	PDF_get_string()
version	PDFlib 9	PDF_get_string() with option version and idx=-1

2.2 Deprecated Options and Keywords which are no longer available in PDFlib 10

Table 2.4 lists API methods for which some options or keywords for an option are no longer available in PDFlib 10.

Table 2.4 Removed PDFlib API options or keywords and their replacements

deprecated option or keyword	deprecated since	replacement option or action
font and text		
PDF_create_textflow(): textwarning	PDFlib 7	errorpolicy
PDF_fit_textline(): locallink, pdflink, weblink	PDFlib 7	matchbox in PDF_fit_textline() and PDF_create_annotation() to create links
PDF_load_font(): autocidfont	PDFlib 9	none; not functional
PDF_load_font(), PDF_info_font() and PDF_fill_textblock(): option and Block property monospace	PDFlib 9	configure TrueType/OpenType fonts or use host fonts
PDF_load_font(): fontwarning	PDFlib 7	errorpolicy
PDF_load_font(): kerning	PDFlib 8	readkerning
text option glyphwarning	PDFlib 7	glyphcheck
PDF_info_textline(): keywords scalex, scaley	PDFlib 9	fitscalex/fitscaley
PDF_info_textline(): keyword unmappedglyphs	PDFlib 8	unmappedchars
PDF_info_textflow(): keyword remainchars	PDFlib 8	none; worked reliably only under certain conditions
PDF_fit/info_textline(), PDF_add/create_textflow() and PDF_fill_textblock(): option features with keywords vrt2 and vert	PDFlib 9.3	none; these features are enabled automatically for fonts in vertical mode
PDF_begin_font(): colorize	PDFlib 10	option colorize of PDF_begin_glyph_ext()
interactive elements		
PDF_create_action(): actionwarning	PDFlib 7	errorpolicy
PDF_create_action(): defaultdir, parameters and operation for type=Launch ¹	PDFlib 9.3	none
PDF_create_annotation(): annotwarning	PDFlib 7	errorpolicy
PDF_create_annotation(): filename and mimetype	PDFlib 9	attachment and options filename and mimetype of PDF_load_asset()
PDF_create_annotation(): popup	PDFlib 10	none; the connection is created automatically if parentname is specified for the pop-up annotation.
PDF_create_annotation(): option template with suboptions normal/rollover/down: keyword viewer	PDFlib 10	none; PDFlib always creates the required appearance stream
PDF_create_field(), PDF_create_fieldgroup(): fieldwarning	PDFlib 7	none; didn't have any effect
PDF_create_field(), PDF_create_fieldgroup(): errorpolicy	PDFlib 9.3	none; didn't have any effect
PDF_create_bookmark(): option destination with sub-options fontstyle and color	PDFlib 6	options fontstyle and textcolor of PDF_create_bookmark()

Table 2.4 Removed PDFlib API options or keywords and their replacements

deprecated option or keyword	deprecated since	replacement option or action
Destination options for <code>PDF_add_nameddest()</code> and for the destination option in <code>PDF_create_action()</code> , <code>PDF_create_annotation()</code> , <code>PDF_create_bookmark()</code> , and <code>PDF_begin/end_document()</code> : options <code>fitbbox</code> , <code>fitheight</code> , <code>fitpage</code> , <code>fitwidth</code> , <code>retain</code>	PDFlib 7	<code>type=visible</code> , <code>fitheight</code> , <code>fitwindow</code> , <code>fitwidth</code> , <code>fixed</code>
option <code>filename</code> and <code>type=file</code>		action option with a GoToR action
option <code>name</code> and <code>type=nameddest</code>		action option with a GoTo action
<code>PDF_create_annotation(): type=Movie</code> ¹	PDFlib 9.3	<code>type=RichMedia</code>
<code>PDF_create_action(): type=Movie</code> ¹	PDFlib 9.3	<code>type=RichMediaExecute</code>
image and PDF import		
<code>PDF_load_image()</code> , <code>PDF_fill_imageblock(): template</code>	PDFlib 8	<code>templateoptions</code>
<code>PDF_load_image()</code> , <code>PDF_fill_imageblock(): createtemplate, iconname</code>	PDFlib 9	<code>templateoptions</code>
<code>PDF_load_image()</code> , <code>PDF_fill_imageblock(): downsamplmask</code>	PDFlib 9.2	none; rendering bug fixed in Acrobat X
<code>PDF_load_image()</code> , <code>PDF_fill_imageblock(): imagewarning</code>	PDFlib 7	<code>errorpolicy</code>
<code>PDF_open_pdi_document()</code> , <code>PDF_open_pdi_page()</code> , <code>PDF_process_pdi()</code> , <code>PDF_fill_pdfblock(): pdiwarning</code>	PDFlib 7	<code>errorpolicy</code>
ICC profiles		
<code>PDF_load_iccprofile(): metadata</code>	PDFlib 9.3	none; XMP for profiles no longer supported
<code>PDF_load_iccprofile(): iccwarning</code>	PDFlib 7	<code>errorpolicy</code>
miscellaneous		
Common XObject options and <code>PDF_begin_page_ext(): transparencygroup</code> with suboptions <code>CS</code> , <code>I</code> , <code>K</code>	PDFlib 8.1	suboptions <code>colorspace</code> , <code>isolated</code> , <code>knockout</code>
<code>PDF_add_table_cell(): checkwordsplitting</code>	PDFlib 8.1	<code>avoidwordsplitting</code>
<code>PDF_begin_document(): moddate</code>	PDFlib 9.2	none; Acrobat Preflight bug fixed
<code>PDF_begin_item()</code> and option <code>tag</code> in many methods: <code>inline</code>	PDFlib 9.2	tagging option <code>direct</code>
<code>PDF_set_option()</code> and many other API methods: <code>errorpolicy=legacy</code>	PDFlib 8	<code>errorpolicy=return</code> or <code>errorpolicy=exception</code>
<code>PDF_set_option(): topdown</code>	PDFlib 9	<code>PDF_begin_page_ext()</code> , <code>PDF_begin_template_ext()</code> or <code>PDF_begin_pattern_ext()</code> with option <code>topdown</code>
<code>PDF_get_option(): topdown</code>	PDFlib 9.3	none; applications must take care of options specified earlier
<code>PDF_set_option(): filenamehandling=legacy</code>	PDFlib 9.3	<code>filenamehandling</code> with explicit encoding <code>name</code> or <code>honorablelang</code>
<code>PDF_set_option(): licence</code> and <code>licencefile</code>	(was never documented)	use corresponding options <code>license</code> and <code>licensefile</code>

1. This feature is deprecated in PDF 2.0 according to ISO 32000-2.

2.3 Deprecated Features in PDF 2.0 and non-ISO Features

Deprecated PDF 2.0 features which are still available in PDF 1.x. PDF 2.0 according to ISO 32000-2 deprecates the features listed in Table 2.5. If any of these features is used, PDFlib emits a warning in PDF 1.x mode and an error in PDF 2.0 mode. It is recommended to avoid these features even in PDF 1.x mode.

Table 2.5 Features deprecated in PDF 2.0 which are still available in PDF 1.x mode

PDFlib features deprecated in PDF 2.0	notes
PDF_begin_document(): permissions with keyword noaccessible	Restricting document accessibility is deprecated in PDF 2.0.
PDF_begin/end_document(): viewerpreferences, suboptions printarea, printclip, viewarea, viewclip	Prepress viewer preferences are deprecated in PDF 2.0.
PDF_begin_page_ext() and PDF_end_page_ext(): separationinfo	Separation dictionaries are deprecated in PDF 2.0.
PDF_create_annotation(): type=Movie	Use type=RichMedia.
PDF_create_action(): type=Movie	Use type=RichMediaExecute.
PDF_create_gstate(): blendmode accepts only a single keyword, but not a list with multiple values	Blendmode arrays are deprecated in PDF 2.0.

Features outside of ISO 32000. The features listed in Table 2.5 were never part of ISO 32000-1. They work only in Acrobat, but not in third-party viewers. If any of these features is used, PDFlib emits a warning in PDF 1.x mode and an error in PDF 2.0 mode. It is recommended to avoid these features since they are not part of standard PDF.

Table 2.6 Features outside of ISO 32000 which are still available in PDF 1.x mode

features outside of ISO 32000	notes
PDF_create_field() and PDF_create_fieldgroup(): barcode	Barcode fields work only in the full version of Acrobat, but neither in Acrobat Reader nor third-party viewers.
PDF_begin_document(): search	An attached search index works only in Acrobat, but not in third-party viewers.
PDF_begin_template_ext(): watermark	Editable watermarks work only in Acrobat, but not in third-party viewers.

2.4 Obsolete Concepts which have been removed

Some concepts are obsolete because there is no longer demand in today's workflows or they haven't been accepted in the marketplace. The items listed in Table 2.7 have been removed in PDFlib 10.

Table 2.7 Obsolete PDF concepts which have been removed from PDFlib

deprecated concept	deprecated since	notes
PDF versions and standards		
PDF 1.3 (1999): PDF_begin_document() with option compatibility=1.3	PDFlib 8.1	not relevant
PDF/X-1:2001: PDF_begin_document() with option pdfx=PDF/X-1:2001	PDFlib 7	superseded by PDF/X-4
PDF/X-1a:2001, PDF/X-3:2002: PDF_begin_document() with option pdfx=PDF/X-1a:2001 and PDF/X-3:2002	PDFlib 8.1	superseded by PDF/X-4
PDF/X-3 standard output intents without embedded ICC profile and resource category StandardOutputIntent	PDFlib 9	superseded by PDF/X-3 and PDF/X-4 with embedded or referenced ICC profile
PDF/X-5g, PDF/X-5pg: PDF_begin_document() with option pdfx=PDF/X-5g and PDF/X-5pg	PDFlib 9.3	not accepted in the marketplace
PDF/VT-2: PDF_begin_document() with option pdfvt=PDF/VT-2	PDFlib 9.3	not accepted in the marketplace
password security		
password encryption: PDF_begin_document() with option userpassword or masterpassword and compatibility=1.4 or 1.5	PDFlib 9.3.1	This combination results in weak RC4 encryption which should be avoided. Create a newer PDF version, preferably PDF 1.7ext8.
font handling		
Multiple Master PostScript Type 1 fonts	PDFlib 9.3	not relevant
resource fork PostScript Type 1 (LWFN) fonts on macOS	PDFlib 9.3	not relevant
SVG fonts	PDFlib 9.3	deprecated in SVG 2.0 and unsupported in most browsers
CEF fonts	PDFlib 9.3	not used as stand-alone fonts
standard CJK fonts and font option/Block property monospace	PDFlib 9	Configure TrueType/OpenType fonts or use host fonts.
CJK TrueType fonts without Unicode cmap table	PDFlib 9.3	Use Unicode-compatible fonts.
PANTONE spot colors		
PANTONE Goe coated/uncoated PANTONE hexachrome coated/uncoated PANTONE solid in hexachrome coated PANTONE solid to process coated PANTONE solid to process coated EURO	PDFlib 9.1	no longer supported by Pantone, Inc.
PANTONE color bridge CMYK PC PANTONE color bridge CMYK EURO PANTONE color bridge uncoated PANTONE solid matte PANTONE process coated EURO PANTONE process uncoated EURO PANTONE process coated PANTONE process uncoated	2010	no longer supported by Pantone, Inc. since 2010
mapping of deprecated PANTONE spot color name suffixes CV, CUV, CVU, CVC and CVP	PDFlib 9.3	old-style PANTONE spot color names are no longer in use

Table 2.7 Obsolete PDF concepts which have been removed from PDFlib

deprecated concept	deprecated since	notes
Interactive features		
Movie annotations ¹ : <code>PDF_create_annotation()</code> with <code>type=Movie</code> and <code>PDF_create_action()</code> with <code>type=Movie</code>	PDFlib 9.3	Use Screen annotations and Rendition actions.
Flash¹		
<code>PDF_load_asset()</code> with <code>type=Flash/Generic/JPEG/PNG</code>	PDFlib 9.3	Flash in RichMedia annotations and Flash-based navigators are no longer supported in Acrobat since December 2020. Use Screen annotations or JavaScript.
<code>PDF_create_annotation()</code> with <code>type=RichMedia</code> and option configuration, <code>suboption</code> instances, <code>suboption</code> params		
<code>PDF_end_document()</code> with option <code>portfolio</code> and <code>suboptions</code> <code>navigator</code> and <code>initialview=custom</code>		
other PDF features		
Reference XObjects: common <code>XObject</code> option <code>reference</code>	PDFlib 9.3	not accepted in the marketplace
page thumbnails: <code>PDF_add_thumbnail()</code>	PDFlib 9	not functional since PDFlib 9.1; PDF viewers create page thumbnails automatically
Open Prepress Interface (OPI) ¹ : common <code>XObject</code> options <code>OPI-1.3</code> , <code>OPI-2.0</code>	PDFlib 9.1	OPI is a concept of the 1980s which has very rarely been used in PDF.
PostScript XObjects ¹ : <code>PDF_begin_template_ext()</code> with option <code>postscript</code>	PDFlib 9.3	not relevant

1. This feature is deprecated or not included in PDF 2.0 according to ISO 32000-2.

2.5 Deprecated Features which are still available in PDFlib 10

Table 2.8 lists deprecated features which are no longer documented, but are still available in PDFlib 10 for the benefit of legacy applications. Users should prepare for future removal of these features and adjust their applications accordingly. New applications should not use any of these features.

Table 2.8 *Deprecated features which are still available in PDFlib 10, but shouldn't be used*

<i>deprecated feature</i>	<i>deprecated since</i>	<i>replacement option or action</i>
Encryption with <code>PDF_begin_document()</code> and the options <code>userpassword/masterpassword</code> with <code>compatibility=1.6</code> , <code>1.7</code> or <code>1.7ext3</code>	PDFlib 10	Remove the password option or increase PDF output compatibility to <code>1.7ext8</code> or above.
CMaps for CJK legacy encodings, i.e. loading a font with a predefined CMap (this affects only non-Unicode-aware language bindings); font option <code>keepnative</code>	PDFlib 10	Switch to Unicode workflow.
PostScript Type 1 fonts	PDFlib 9.3.1	Use TrueType or OpenType fonts.
PDF/X-1a:2003: <code>PDF_begin_document()</code> with option <code>pdfx=PDF/X-1a:2003</code>	PDFlib 9.3	Use PDF/X-4.
<code>PDF_begin_font()</code> : option <code>colorized</code>	PDFlib 10	Use option <code>colorized</code> of <code>PDF_begin_glyph()</code> ; the color status can now be specified for individual glyphs instead of only for all glyphs in the font.
<code>PDF_begin_template_ext()</code> : option <code>watermark</code>	PDFlib 10	Create a template without the watermark option.
<code>PDF_info_font()</code> : option <code>shapingsupport</code>	PDFlib 9.3.1	This keyword couldn't be used reliably to test for shaping support.

3 Configuration Changes

3.1 Modified Default Values

The default values of some options have been modified according to Table 3.2. This allows shorter code, but in a few cases the options must be supplied with the desired value if the new defaults don't match your requirements.

Table 3.1 PDFlib features which require configuration changes

PDFlib feature	required change if the new default doesn't match your requirements
The default PDF compatibility has been increased from PDF 1.7 to PDF 1.7ext8 which supports stronger encryption, RichMedia annotations and other features.	If you must create PDF 1.7 output (the default in PDFlib 9) use <code>PDF_begin_document()</code> with option <code>compatibility=1.7</code> .
<code>PDF_load_font()</code> and implicit font loading: fonts are embedded by default	Fonts are embedded by default. Use the option <code>embedding=false</code> to disable font embedding if you really want that or must use deprecated PostScript Type 1 fonts for which no embeddable outlines are available. The default of <code>skipembedding</code> is now <code>{fstype latincore}</code> (except in PDF/A, PDF/X and PDF/UA mode where the default is still empty). This means that fonts with embedding restrictions are silently processed without embedding instead of raising an exception; similar for Standard Latin fonts without embeddable outlines.
<code>PDF_load_image()</code> with RGB images: the sRGB ICC profile is now applied by default	sRGB is useful for achieving more accurate color automatically. In rare cases where sRGB is not desired it can be disabled with <code>iccprofile=none</code> . This is required for the thumbnail option of <code>PDF_load_asset()</code> .
<code>PDF_load_graphics()</code> and option <code>templateoptions</code> : templates are created by default	PDFlib now creates a Form XObject (template) for SVG by default. The previous behavior can be achieved with the <code>inline</code> option.
<code>PDF_set_option()</code> : the default value of the <code>stringformat</code> option is now <code>utf8</code> in Perl, PHP, Python and Ruby	see Chapter 4
Option <code>errorpolicy</code> of <code>PDF_set_option()</code> and many other API methods: the new default is <code>return</code> .	Set <code>errorpolicy=return</code> and check error return values or set <code>errorpolicy=exception</code> if it is acceptable to give up the output document in case of problems.
text output in fonts with OpenType features with the <code>features</code> option of <code>PDF_fit/info_textline()</code> , <code>PDF_add/create_textflow()</code> , and <code>PDF_fill_textblock()</code> : the <code>ccmp</code> feature is now enabled by default	Use <code>features={noccmp}</code> to disable the <code>ccmp</code> feature.

3.2 Other Configuration Changes

In some situations you must adjust source code and configuration according to Table 3.2.

Table 3.2 PDFlib features which require configuration changes

PDFlib feature	required change
<code>PDF_create_annotation()</code> with <code>type=Caret</code> , <code>FreeText</code> , <code>Line</code> (only if <code>showcaption=true</code>)	Access to the font <code>NotoSans-Regular</code> must be configured unless the <code>font</code> option is supplied. ¹
<code>PDF_create_annotation()</code> with <code>type=Stamp</code>	Access to the font <code>NotoSans-Bold</code> must be configured unless the <code>font</code> option is supplied. ¹
<code>PDF_load_asset()</code> with <code>type=Sound</code> or <code>Video</code>	The option <code>mimetype</code> is now required.
names of form fields	Field names created with <code>PDF_create_field()</code> must be unique in the document. Fields with synchronized values can be created with <code>PDF_create_fieldgroup()</code> and a suitable <code>fieldtype</code> option.
8-bit encodings	<p>The following encoding definitions are no longer available internally in PDFlib, but only as external files which must be configured appropriately (see PDFlib Tutorial):</p> <p>iso8859-2, iso8859-3, iso8859-4, iso8859-5, iso8859-6, iso8859-7, iso8859-8, iso8859-9, iso8859-10, iso8859-13, iso8859-14, iso8859-15, iso8859-16, cp1250, cp1251, cp1253, cp1254, cp1255, cp1256, cp1257, cp1258</p>
Standard Type 1 font Courier	<p>PDFlib 9 treated the Standard Type 1 font Courier in a special way to make certain glyphs beyond ISO 8859-1 available in Acrobat even without font embedding. However, this technique isn't backed by ISO 32000 and is not supported by other PDF viewers.</p> <p>Workaround: configure an embeddable version of Courier.</p>

1. These fonts are included in the PDFlib distribution package. The PDFlib Tutorial describes several methods for font configuration, especially `searchpath`. Since these fonts don't include CJK glyphs a suitable CJK font should be supplied to the `font` option if CJK text is used with `type=Caret`, `FreeText`, `Line` or `Stamp`.

4 Binding-specific Changes in PDFlib 10

4.1 C Language Bindings

Table 4.1 PDFlib features which require changes in C applications

PDFlib feature	required change
The errorhandler callback for <code>PDF_new2()</code> no longer supports the <code>errortype</code> parameter which has been unused since PDFlib 8.	Change your custom errorhandler for <code>PDF_new2()</code> from <pre>typedef void (*errorproc_t) (PDF *p1, int errortype, const char *msg);</pre> to <pre>typedef void (*errorproc_t) (PDF *p1, const char *msg);</pre>

4.2 C++ Language Bindings

Table 4.2 PDFlib features which require changes in C++ applications

PDFlib feature	required change
Removed the <code>PDFCPP_USE_PDFLIB_NAMESPACE</code> macro which disabled namespace support for PDFlib 7 compatibility.	Use the following in your application code: <code>using namespace pdflib;</code>
Removed custom string types and the <code>PDFCPP_PDFLIB_WSTRING</code> macro which disabled <code>wstring</code> support in favor of <code>string</code> for PDFlib 7 compatibility.	Use one of the standard C++ string types <code>wstring</code> , <code>u8string</code> , <code>u16string</code> , <code>u32string</code> , or <code>string</code>

4.3 Objective-C Language Binding for macOS and iOS

Table 4.3 PDFlib features which require changes in Objective-C applications

PDFlib feature	required change
The name of the PDFlib framework is now identical for macOS and iOS.	iOS applications only: change the framework name <code>PDFlib_ios</code> to <code>PDFlib</code> in the <code>#import</code> statement.

4.4 Perl Language Binding

Table 4.4 PDFlib features which require changes in Perl applications

PDFlib feature	required change
<code>PDF_set_option()</code> : the default value of the <code>stringformat</code> option is now <code>utf8</code> .	No change required for the common case of Unicode-based applications which already set <code>stringformat=utf8</code> . Applications which work with 8-bit encodings must set <code>stringformat=legacy</code> .

4.5 PHP Language Binding

Table 4.5 PDFlib features which require changes in PHP applications

PDFlib feature	required change
<i>PDF_set_option(): the default value of the stringformat option is now utf8.</i>	<i>No change required for the common case of Unicode-based applications which already set stringformat=utf8. Applications which work with 8-bit encodings must set stringformat=legacy.</i>
<i>The functional PDFlib API (deprecated since PDFlib 8) has been removed in favor of the object-oriented interface.</i>	<i>Convert application code to the object-oriented interface.</i>
<i>The delete() method (which was no-op anyway) has been removed.</i>	<i>Remove all calls to PDFlib->delete() from application code.</i>

4.6 Ruby Language Binding

Table 4.6 PDFlib features which require changes in Ruby applications

PDFlib feature	required change
<i>PDF_set_option(): the default value of the stringformat option is now utf8.</i>	<i>No change required for the common case of Unicode-based applications which already set stringformat=utf8. Applications which work with 8-bit encodings must set stringformat=legacy.</i>

5 PDFlib History

Table 5.1 Release history of PDFlib, PDFlib+PDI and PPS

<i>PDFlib version</i>	<i>release date</i>
<i>PDFlib 4</i>	2001
<i>PDFlib 5</i>	2003
<i>PDFlib 6</i>	2004
<i>PDFlib 7</i>	2006
<i>PDFlib 8</i>	2009
<i>PDFlib 8.1</i>	2011
<i>PDFlib 9</i>	2013
<i>PDFlib 9.1</i>	2016
<i>PDFlib 9.2</i>	2019
<i>PDFlib 9.3</i>	2020
<i>PDFlib 9.3.1</i>	2021
<i>PDFlib 10</i>	2021